

SAFETY DATA SHEET

conforms to Regulation (EC) No. 1907/2006

1 IDENTIFICATION OF THE PRODUCT AND THE COMPANY

1.1. **Product:** Drawing Ink 4300.0000

1.2. **Company:** Royal Talens

Sophialaan 46, 7311 PD, Apeldoorn, the Netherlands P.O. Box 4, 7300 AA, Apeldoorn, the Netherlands

Telephone +31 (0)55 - 5274700 Telefax +31 (0)55 - 5215286

www.talens.com info@talens.com

2 HAZARD IDENTIFICATION

This product is not considered to be a hazardous product under Directive 1999/45/EC and Regulation (EC) No. 1272/2008.

3 COMPOSITION AND INFROMATION ON INGREDIENTS

No reportable components.

4 FIRST-AID MEASURES

Inhalation: N.a.

Skin contact: Wash with soap and water.

Eye contact: Flush with water, consult a physician.

Ingestion: Consult a physician.

5 FIRE-FIGHTING MEASURES

N.a.

6 ACCIDENTAL RELEASE MEASURES

Absorb on a suitable substrate. Clean area with water.

7 HANDLING AND STORAGE

N.a.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Wash hands after use.

Product: Drawing Ink Rev. date: August 3, 2010

Art.no.: 4300.0000 Page: 1/



9 PHYSICAL AND CHEMICAL PROPERTIES

Characterization: Solution of organic dyes and shellac in water exclusively intended for

applications on paper (white and black are based on pigments instead of

dyes).

Form: Liquid

Odour:

pH: 7.5-8.5 (20°C) **Viscosity:** approx. 3 mPa.s (20°C)

Boilingpoint/-range*: approx. 100 °C Meltingpoint/-range*: °C Flashpoint*: n.a. °C

Density*: 1.03-1.32 g/cm³ (20°C)

Solubility in water*: soluble/mixable g/l

Other information:

10 STABILITY AND REACTIVITY

N.a.

11 TOXICOLOGICAL INFORMATION

N.a.

12 ECOLOGICAL INFORMATION

Avoid contamination of sewerage.

13 DISPOSAL CONSIDERATIONS

Comply with local regulations.

14 TRANSPORT INFORMATION

No transport classification. No restriction.

15 REGULATORY INFORMATION

This product is not considered to be a hazardous preparation under directive 1999/45/EC and Regulation (EC) No. 1272/2008.

16 OTHER INFORMATION

Product: Drawing Ink Rev. date: August 3, 2010

Art.no.: 4300.0000 Page: 2/2

^{*} items tested in accordance with 67/548/EC